

**Specialists in Industrial & Automotive Oil**

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046  
130 Sarel Baard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661-9888  
Fax: (012) 661-9882  
E-mail: viscol@jafrika.com  
Website: www.viscol.co.za

Document Number:

**TDS006****SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)***CASTSTRIP 650****Product Description:**

A low viscosity petroleum based mould and shutter releasing agent formulated exclusively for quick releasing properties. It is particularly effective during premature stripping of moulds and shutters.

**Product Application:**

1. Steel moulds used in the manufacture of kerb stones and railway sleepers; etc.
2. Steel and hardboard shuttering.
3. Apply product every time used.

**Product Packaging:**

20 litre and 210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects, especially in those difficult situations where a special formulation may be required. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 19/08/2001	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: