

**Specialists in Industrial & Automotive Oil**

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document Number:

TDS012**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOL PLASTERLOCK****Product Description:**

PLASTERLOCK is free from halogens and other aggressive constituents and is particularly suitable for the modification of cement, lime and gypsum based mortars. It can also be used for the manufacture of building adhesives, and towelling and levelling screeds. PLASTERLOCK will bind plaster onto any surface and can be used for repairing broken corners on steps. Instead of hacking and chipping surfaces, use PLASTERLOCK for quick and effective bonding of plaster to smooth surfaces. When mixed with cement, the PLASTERLOCK compound acts as a good tile adhesive.

Product Application:

Apply a scratch coat of plaster onto wet PLASTERLOCK. Further plaster may be applied once the scratch coat is dry, without having to use PLASTERLOCK again. Apply PLASTERLOCK to surface with the roll-on method when using gypsum based plaster. PLASTERLOCK may also be used as a general glue at home, schools and workshops.

Product Packaging:

2,5 litre containers
5 litre containers
20 litre containers
210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

Page: 1/1	Date: 18/10/2001	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: