

**Specialists in Industrial & Automotive Oil**

Viscol cc  
 Reg No: 1987/028096/23  
 Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046  
 130 Sarel Baard Crescent  
 Gateway Industrial Park  
 Rooihuiskraal

Tel: (012) 661-9888  
 Fax: (012) 661-9882  
 E-mail: viscol@iafrica.com  
 Website: www.viscol.co.za

Document Number:

**TDS014****SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)*

**TILOCRETE (ALTERNATIVE NAME: FLOORSTRIP)****Description:**

Tilocrete (Floorstrip) is a mould release oil formulated specifically for the automatic production of Concrete Roofing Tiles from aluminium pallets. This petroleum product includes additives that enhance releasing properties, protects aluminium moulds from staining and provides extremely clean parting after the curing process. Wetting agents provide for a very thin tenacious film that results in good coverage.

**Performance Benefits:**

- Reduced spray nozzle size increases economical usage
- Odour is sweet and pleasant
- Extremely good parting properties
- Non-staining of pallets
- Ready-to-use mould release agent

**Application:**

Easily applied by automatic spray

**Typical Physical Properties:**

Neutral Number	D974 MOD	mg KOH/g	+ - 11,2
Viscosity @ 40°C	ASTM D445	cSt	6
ASTM Colour Test	ASTM D1500		6
Specific Gravity @ 20°C	ASTM D1298	kg/l	0,85
Open Cup Flash Point	ASTM D92	°C	65

**Product Packaging:**

Bulk - Product Code 019220  
 210 litre drums - Product Code 019221

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

**The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.**

Page: 1/1	Date: 01/12/2000	Supersedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by:
		Authorised by: