

**Specialists in Industrial & Automotive Oil**

Viscol cc
 Reg No: 1987/028096/23
 Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
 130 Sarel Baard Crescent
 Gateway Industrial Park
 Rooihuiskraal

Tel: (012) 661-9888
 Fax: (012) 661-9882
 E-mail: viscol@iafrica.com
 Website: www.viscol.co.za

Document Number:

TDS016A**SUBJECT: OIL SPECIFICATIONS**

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

VISCOL 15W40 CH-4/SJ MULTIGRADE ENGINE OIL (SUPERIOR)**Description & Characteristics:**

A superior quality SAE 15W40 extra heavy duty oil, recommended for naturally aspirated and turbo-charged diesel engines, petrol engines, hydrostatic transmissions and hydraulic systems of most contractor and commercial automotive equipment.

Having a Viscosity Index improved for stay-in-grade performance and considerable quality reserve, this mixed fleet oil exceeds the performance requirements of a number of statutory and manufacturers specifications/standards.

Viscol 15W40 CH-4/SJ Multigrade Oil meets the following classifications:

| VISCOL CH-4/SJ 15W40 MULTIGRADE OIL | TYPICAL |
|---|---------|
| Viscosity, mPas at -15°C max | 3500 |
| Viscosity, mm ² /s at 40°C(cSt) | 110 |
| Viscosity, mm ² /s at 100°C(cSt) | 14,6 |
| Viscosity Index | 150 |
| Pour Point, °C max | -25 |
| Flash Point, °C min | 216 |
| Sulphated Ash, % m/m | 1,5 |
| Total Base Number, mg KOH/g | 14 |

| | | |
|-----------------|---------------------------|--------------------|
| Page: 1/2 | Date: 31/04/2003 | Supersedes: New |
| SOP ref: New | Compiled by: Alex Hime | Checked by: |
| | | Authorised by: |



Specialists in Industrial & Automotive Oil

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document Number:

TDS016A

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

Performance Level:

API Service Classifications CH-4, CG-4, CF-4, SJ, SL
SABS 1361, 400-A, 400 & 399
MIL-L-2104D and MIL-L-46152B
CCMC requirements.
Ford ESE-M2C144-A, ESE-M2C-87-A/88-A, ESN-M2C121-B, ESE-M2C153-C, ESEE-M2C1004-A, SM-2C1016-A/1017-A and SSM-2C9001-AA
Caterpillar API CF/to -2
Leyland BLS-OL-02
Mack EO-M
Daimler-Benz 228.2/3
ADE Annexure C, D and E
ACEA Service Class. E7 - 04

Benefits:

Good engine cleanliness.
Protection against the effects of high sulphur fuels.
Excellent protection against wear, rust and corrosion.
Lower fuel and oil consumption.
Extended drain period capability.
Easy cold starting.
Mixed fleet application.

Applications:

Recommended for naturally aspirated and turbo-charged diesel engines, petrol engines, certain hydrodynamic transmissions and hydraulic systems of most contractor and commercial automotive equipment.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

| | | |
|-----------------|---------------------------|--------------------|
| Page: 2/2 | Date: 31/04/2003 | Supercedes: New |
| SOP ref: New | Compiled by: Alex Hime | Checked by: |
| | | Authorised by: |