



Specialists in Industrial & Automotive Oil

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document
Number:

TDS020

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

VISCOL ANTIFREEZE

Description & Characteristics:

Viscol Antifreeze is a high quality product containing anti-corrosion additives. It reduces the freezing point of the cooling water and increases the boiling point. The anti-corrosion additives give protection to Aluminium, copper, cast iron and other metals used in cooling systems.

Specifications:

Mercedes Benz Approval Sheet 325.0
SABS 1251 - 1979
Cummings and ADE Sheet GB 94/01 Page 11

Physical Properties:

VISCOL ANTIFREEZE	
Relative Density @ 15°C	1,1135
Reserve Alkalinity ml 0,1, NHCL	17,0
Flash Point(°C)	117,0
Boiling Point(°C)	170,0

Mixture Ratios:

33% Dilution: -18 deg C protection*
50% Dilution: -34 deg C protection*

*These temperatures based on using a 103KPA radiator cap.

Packaging:

210 litre drums
20 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 28/11/2001	Supercedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by: