

**Specialists in Industrial & Automotive Oil**

Viscol cc  
 Reg No: 1987/028096/23  
 Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046  
 130 Sarel Baard Crescent  
 Gateway Industrial Park  
 Rooihuiskraal

Tel: (012) 661-9888  
 Fax: (012) 661-9882  
 E-mail: viscol@iafrica.com  
 Website: www.viscol.co.za

Document  
 Number:

**TDS028****SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)*

**VISCOL HEAT TRANSFER OIL 32, 100****Description**

Viscol Heat Transfer oils are premium quality oils intended for application in enclosed heat transfer systems with bulk oil temperatures of up to 316° C. The ability to flow rapidly at low temperatures ensures quick circulation at start-up and less risk of local overheating. Heat Transfer oils are formulated using highly refined high viscosity index paraffinic base oils.

**Advantages**

Good oxidation and thermal stability over wide operating temperature.  
 Good corrosion protection.  
 No sludge formation.

**Characteristics****Heat Transfer 32**

VISCOSITY (cSt)		POUR PIONT	FLASH POINT
40°C	100°C	°C	°C
30.99	5.146	-21	216

**Heat Transfer 100**

VISCOSITY (cSt)		POUR PIONT	FLASH POINT
40°C	100°C	°C	°C
100.3	10.91	-9	234

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 12/12/2003	Supercedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by: