

**Specialists in Industrial & Automotive Oil**

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document
Number:**TDS045****SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOL RED/BLUE DEGREASING FLUID**

Viscol Red/Blue Degreasing fluid consists of a blend of solvents and surfactants, which enables the product to be water-soluble.

Application :**RED: Used on vehicle engines and applications which are sensitive to degradation, example: paint .**

Red Degreasing fluid should be applied to surfaces by brush or spray and be left for approximately 5 minutes to allow the product to react to grease and dirt. The product can then be washed off with water.

BLUE: Used on factory floors and other applications which are NOT sensitive to degradation.

Blue Degreaser is a very powerful solvent based cleaner. Application is the same as for red degreaser.

Benefits :

1. Powerful solvent action
2. Dissolves or loosens oil and grease deposits
3. Simple spray or brush application
4. Easily removed by water wash

Description :

Flash Point (Abel) °C min 50
Initial Boiling Point °C min 150
Final Boiling Point °C max 280

Packaging

200 litre drums
20 litre pails

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his own use. The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 29/01/2000	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: