



Specialists in Industrial & Automotive Oil

Viscol cc	P.O. Box 7182, Centurion, 0046	Tel: (012) 661-9888
Reg No: 1987/028096/23	130 Sarel Baard Crescent	Fax: (012) 661-9882
Vat Reg : 4380103046	Gateway Industrial Park	E-mail: viscol@iafrica.com
	Rooihuiskraal	Website: www.viscol.co.za

Document Number:

TDS088

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

VISCOL ROCKDRILL OIL 100, 150

Description & Characteristics :

Viscol Rockdrill oils are high viscosity index oils blended with anti-wear and anti-corrosion additives. These oils are used extensively on wagon drills.

Performance Benefits :

Viscol Rockdrill Oils have good resistance to water-wash and maintain excellent lubrication. Ideal protection against rust and corrosion, have good extreme pressure and anti-wear properties.

Application :

Viscol Rockdrill Oils for percussion tools particularly on wagon drill units.

Physical Properties :

ISO GRADE	100	150
Viscosity cSt @ 40°C	90 - 110	150
Flash Point (COC)	230	240
Timken OK Load . . . kg	27	27

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

Page:	1/1	Date:	06/01/2001	Supercedes:	New
SOP ref:	New	Compiled by:	Alex Hime	Checked by:	Authorised by: