

**Specialists in Industrial & Automotive Oil**Viscol Oil Company cc
Reg No CK 87/28098/23P.O. Box 763, Fourways, 2055
130 Sarel Baard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Cell: 083 326 4151

Document Number:

TDS108**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOL WHEEL BEARING (WB) GREASE****Description & Characteristics :**

Viscol WB Grease is a premium quality lithium soap based grease made from heavy viscosity base oils containing anti-oxidant, anti-rust and extreme pressure additives.

Specifications :

Viscol WB Grease meets the S.A.B.S. 1014 Specification.

Performance Benefits :

Viscol WB Grease is an excellent general purpose grease for heavy duty wheel bearings. This grease is also intended for general industrial lubrication of plain and roller bearings up to an operating temperature of 130°C, depending on the speed/temperature rating laid down by the bearings manufacturer.

Typical Physical Properties :

NLGI No ...	2
Penetration @ 25°C	265 – 295
Drop Point °C	185
Oil Viscosity @ 40°C	1000
Timken OK Value kg	32
Wheel Bearing Leakage. Max % m	1

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

Page: 1/1	Date: 01/09/10	Supercedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by: