

**Specialists in Industrial & Automotive Oil**

Viscol cc	P.O. Box 7182, Centurion, 0046	Tel: (012) 661-9888
Reg No: 1987/028096/23	130 Sarel Baard Crescent	Fax: (012) 661-9882
Vat Reg: 4380103046	Gateway Industrial Park	E-mail: viscol@iafrica.com
	Rooihuiskraal	Website: www.viscol.co.za

Document Number:

TDS064**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOL AXLE OIL ISO 150****Description and Characteristics**

Anti-wear lubricating oil for railway car and locomotive axle.

These oils provide outstanding component life, system cleanliness, oxidation stability, demulsibility, as well as protection against rust and corrosion.

They have a low Pour Point, high resistance to foaming and air entrapment, pass 12 stages of the F.Z.G. Spur Gear Test, show minimum wear in Vickers V - 104C pump tests (IP, DIN and ASTM methods), even when contaminated with water they perform equally well. Viscol oils are easily filterable and the anti-wear additive used is stabilised which explains their excellent multi-metal compatibility.

Physical Characteristics

ISO GRADE	150
Viscosity @ 40°C	146
Viscosity @ 100°C	15.3
Viscosity Index	150
Pour Point °C	-27
Flashpoint °C (PENSKY – MARTENS Closed cup)	243

Benefits

- ◆ Rust and oxidation inhibited.
- ◆ Mineral oil having good wicking and oxidation stability properties.
- ◆ Balanced formulation for the best performance.
- ◆ Wide range of applications in industrial and automotive equipment.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

Page: 1/1	Date: 18/03/2000	Supercedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by:
		Authorised by: