



Document Name:

TDS002

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

BRICKLITE

Product Description:

A low viscosity mineral lubricating oil containing blends of light process oils and medium flash kerosenes. A formulation exclusively manufactured for the clay brick industry for extrusion of bricks. Bricklite has a dual function and may also be used in a fuel firing system.

Gross Calorific Value @ 15 °C, KJ/kg	46050
Viscosity, mm ² /s @ 40 °C	4,7

Product Application:

1. Used in the process of clay brick extrusion.
2. Used in a fuel firing system.
3. Simple handling equipment as a result of low viscosity.
4. Easy atomisation and control.

Product Packaging:

210 litre and bulk

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

Page: 1/1	Date: 15/12/2011	Supersedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: