



Document  
Number:

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za

**TDS004**

**SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)*

## CASTRIP 950

### Description and Characteristics

Castrip 950 is a ready to use mould release oil for the production of railway sleepers, lintels and concrete slabs. The additives used in Castrip 950 enhance the releasing properties, protect the moulds from staining and provides an extremely clean release after curing.

### Physical Characteristics

Viscosity at 40°C cST	6
Specific Gravity at 20°C kg/1	0.85
Open cup flash point ASTM D92°C	65

### Benefits

Extremely good releasing properties.  
Non staining of pallets.  
Good coverage.  
Ready to use.

### Application

Can be applied by swab, brush or spray.

### Specifications

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

Page: 1/1	Date: 15/12/2011	Supersedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: