



Document Number:

TDS005

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

CASTRIP 550

Product Description:

A low viscosity petroleum based mould and shutter releasing agent formulated exclusively for quick releasing properties. It is particularly effective during pre-mature stripping of moulds and shutters. This product is boosted with fatty material for those stubborn moulds.

Product Application:

1. Steel moulds used in the manufacture of kerb stones and railway sleepers; etc.
2. Steel and hardboard shuttering.
3. Apply product every time used.

Product Packaging:

20 litre and 210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects, especially in those difficult situations where a special formulation may be required. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/12/2011	Supercedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: