



Document Number:

**TDS010**

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za

**SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)*

## MULTISTRIP A2

### Description

A low viscosity petroleum blend incorporating releasing additives for excellent off-shutter finishes. All-round and general purpose effective shutter and mould release agent. Non-staining and colourless.

### Application

1. Apply one coat by spray, roller or brush.
2. Timber, steel, fibreglass and concrete moulds.
3. 25 m<sup>2</sup> coverage per litre.
4. Does not affect plaster.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use. The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/12/2011	Supercedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: