



Document Number:

TDS012

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

VISCOL PLASTERLOCK

Product Description:

PLASTERLOCK is free from halogens and other aggressive constituents and is particularly suitable for the modification of cement, lime and gypsum based mortars. It can also be used for the manufacture of building adhesives, and towelling and levelling screeds. PLASTERLOCK will bind plaster onto any surface and can be used for repairing broken corners on steps. Instead of hacking and chipping surfaces, use PLASTERLOCK for quick and effective bonding of plaster to smooth surfaces. When mixed with cement, the PLASTERLOCK compound acts as a good tile adhesive.

Product Application:

Apply a scratch coat of plaster onto wet PLASTERLOCK. Further plaster may be applied once the scratch coat is dry, without having to use PLASTERLOCK again. Apply PLASTERLOCK to surface with the roll-on method when using gypsum based plaster. PLASTERLOCK may also be used as a general glue at home, schools and workshops.

Product Packaging:

2,5 litre containers
5 litre containers
20 litre containers
210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

Page: 1/1	Date: 145/12/2011	Supercedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: