



Document Number:

**TDS013**

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za

**SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)*

## VISCOL SHUTTERSTRIP B

### Product Description:

A low viscosity solution of highly refined petroleum and waxy based products. Besides good releasing properties, this product protects wood and hardboard shutters, prevents rusting and cement build-up on steel shutters. Adverse weather conditions does little to wash off or drying out.

### Product Application:

1. Wood, hardwood and steel shuttering used when constructing columns, beams and decking, etc.
2. Conservative usage of every three to four instances.
3. For steel shutters where concrete is vibrated, apply every second time.
4. Apply to scaffolding, pumps and other equipment as a layer protector.

### Product Packaging:

20 litre and 210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects, especially in those difficult situations where a special formulation may be required. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

Page: 1/1	Date: 15/12/2011	Supercedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: