



Document Number:

TDS014Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
(in accordance with ISO 9001 & 14001)

TILOCRETE (ALTERNATIVE NAME: FLOORSTRIP)

Description:

Tilocrete (Floorstrip) is a mould release oil formulated specifically for the automatic production of Concrete Roofing Tiles from aluminium pallets. This petroleum product includes additives that enhance releasing properties, protects aluminium moulds from staining and provides extremely clean parting after the curing process. Wetting agents provide for a very thin tenacious film that results in good coverage.

Performance Benefits:

- Reduced spray nozzle size increases economical usage
- Odour is sweet and pleasant
- Extremely good parting properties
- Non-staining of pallets
- Ready-to-use mould release agent

Application:

Easily applied by automatic spray

Typical Physical Properties:

Neutral Number	D974 MOD	mg KOH/g	+/- 11,2
Viscosity @ 40°C	ASTM D445	cSt	6
ASTM Colour Test	ASTM D1500		6
Specific Gravity @ 20°C	ASTM D1298	kg/l	0,85
Open Cup Flash Point	ASTM D92	°C	65

Product Packaging:

Bulk - Product Code 019220
210 litre drums - Product Code 019221

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/12/2011	Supercedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: