



Document Number:

**TDS015**Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046P.O Box 71382, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
RooihuiskraalTel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)*

## UNISTRIP

### Product Description:

A medium viscosity petroleum based mould and shutter releasing agent. Boosted additives ensure a good clean strip. Non evaporation agents prevent loss of product whilst moulds and shutters are in the sun.

### Product Application:

1. Steel shutters.
2. Steel moulds.
3. Fibreglass shutters.
4. Fibreglass moulds.

### Product Packaging:

20 litre and 210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects, especially in those difficult situations where a special formulation may be required. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/12/2011	Supersedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: