



Document Number:

TDS 016 AViscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with ISO 9001 & 14001)***VISCOL 15W40 CH-4/SJ MULTIGRADE ENGINE OIL (SUPERIOR)****Description & Characteristics:**

A superior quality SAE 15W40 extra heavy duty oil, recommended for naturally aspirated and turbo-charged diesel engines, petrol engines, hydrostatic transmissions and hydraulic systems of most contractor and commercial automotive equipment.

Having a Viscosity Index improved for stay-in-grade performance and considerable quality reserve, this mixed fleet oil exceeds the performance requirements of a number of statutory and manufacturers specifications/standards.

Viscol 15W40 CH-4/SJ Multigrade Oil meets the following classifications:

VISCOL CH-4/SJ 15W40 MULTIGRADE OIL	TYPICAL
Viscosity, mPas at -15°C max	3500
Viscosity, mm ² /s at 40°C(cSt)	110
Viscosity, mm ² /s at 100°C(cSt)	14,6
Viscosity Index	150
Pour Point, °C max	-25
Flash Point, °C min	216
Sulphated Ash, % m/m	1,5
Total Base Number, mg KOH/g	14

Page: 1/2	Date: 15/12/2011	Supersedes: New	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by:



Document Number:

TDS 016 AViscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with ISO 9001 & 14001)***Performance Level:**

API Service Classifications CH-4, CG-4, CF-4, SJ, SL
SABS 1361, 400-A, 400 & 399
MIL-L-2104D and MIL-L-46152B
MAN M3275
JASO DH-1 (pending), VOLVO VDS -3 (pending), Cummins 20076/77/78 (pending)
Ford ESE-M2C144-A, ESE-M2C-87-A/88-A, ESN-M2C121-B, ESE-M2C153-C, ESEE-M2C1004-A, SM-2C1016-A/1017-A and SSM-2C9001-AA
Caterpillar API CF/to -2
Leyland BLS-OL-02
Mack EO-M Plus (pending)
Daimler-Benz 228.2/3
ADE Annexure C, D and E
ACEA Service Class. E7 - 04

Benefits:

Good engine cleanliness.
Protection against the effects of high sulphur fuels.
Excellent protection against wear, rust and corrosion.
Lower fuel and oil consumption.
Extended drain period capability.
Easy cold starting.
Mixed fleet application.

Applications:

Recommended for naturally aspirated and turbo-charged diesel engines, petrol engines, certain hydrodynamic transmissions and hydraulic systems of most contractor and commercial automotive equipment.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 2/2	Date: 15/12/2011	Supersedes: New	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by: