



Document Number:

TDS 024Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with ISO 9001 & 14001)***VISCOL BRAKE FLUID****Description & Characteristics:**

Viscol Brake Fluid is an extra heavy duty fluid which is recommended for all transport vehicles, all disk and drum brakes. Viscol Brake Fluid is a high boiling brake and clutch fluid of minimum boiling point 260 deg C, meeting SAE J1703 and United States Federal Motor Vehicle Safety Standard No116 Dot 4.

Physical Properties:

| | |
|--------------------|-----------|
| VISCOL BRAKE FLUID | |
| Density @ 20°C | 1,04 KG/L |
| Flash Point (°C) | 145 |

Packaging:210 litre drums
20 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use. The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

| | | | |
|-----------------------|---------------------------|--------------------|----------------|
| Page: 1/1 | Date: 15/11/2011 | Supersedes: New | |
| SOP ref: (Rev. 02) | Compiled by: Alex Hime | Checked by: | Authorised by: |