



Document Number:

TDS 026 A

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

VISCOL GL5 80W90 AUTOMOTIVE GEAR OIL

Description & Characteristics:

This is a premium quality gear lubricant specially recommended for synchromesh gearboxes. It contains sulphur-phosphorus EP and other additives exceeding the requirements of the U.S. Military Specifications MIL-L-2105D.

VISCOL 80W90 AUTOMOTIVE GEAR OIL	
Viscosity @ 40°C (cSt)	130
Viscosity @ 100°C (cSt)	13,9
Viscosity Index	95
Flash Point(°C)	164
Pour Point(°C)	-35

Performance Level:

API Service Classification GL-5.
MIL-L-2105D
Approved by Ford, Volkswagen and Zf
Daimler-Benz 235.1 (GX 80W-A)
MAN 342N

Benefits:

1. Full protection to transmissions with bronze components.
2. Excellent low temperature fluidity.
3. Easy gear change.
4. Major equipment Builder acceptance.

Applications:

Suitable for transmission/axle combinations synchromesh gearboxes and other applications which require a relatively low level of EP additives.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

Page: 1/1	Date: 15/11/2011	Supersedes: New
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by: Authorised by: