



Document
Number:

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

TDS 036

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

VISCOL TWO STROKE ENGINE OIL

Description

Viscol Two Stroke Engine Oil is a high quality engine lubricant formulated for hot running two stroke engines. Fuel/oil ratios as recommended by the manufacturer of up to 50 : 1 with both leaded and unleaded petrol. It is readily miscible with fuel and contains selected additives to give good piston cleanliness, thermal stability, anti-wear and corrosion protection performance.

Specifications

Density @ 20°C	0,876
Viscosity cSt @ 40°C	72,5
Viscosity cSt @ 100°C	10,22
Viscosity Index	125
Flash Point (COC)°C	72
Pour Point (°C)	-9

Application

Viscol Two Stroke Oil is suitable for use in all air-cooled and water-cooled engines used in mopeds, scooters, motor cycles, snow mobiles, outboard motors (**but NOT large outboards demanding NMMA TC-W3 approved grades**), stand-by generators, chainsaws, lawnmowers and others.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/12/2011	Supercedes: New	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by: