



Document
Number:

TDS045

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

VISCOL RED/BLUE DEGREASING FLUID

Viscol Red/Blue Degreasing fluid consists of a blend of solvents and surfactants, which enables the product to be water-soluble.

Application :

RED: Used on vehicle engines and applications which are sensitive to degradation, example: paint .

Red Degreasing fluid should be applied to surfaces by brush or spray and be left for approximately 5 minutes to allow the product to react to grease and dirt. The product can then be washed off with water.

BLUE: Used on factory floors and other applications which are NOT sensitive to degradation.

Blue Degreaser is a very powerful solvent based cleaner. Application is the same as for red degreaser.

Benefits :

1. Powerful solvent action
2. Dissolves or loosens oil and grease deposits
3. Simple spray or brush application
4. Easily removed by water wash

Description :

Flash Point (Abel) °C min	50
Initial Boiling Point °C min	150
Final Boiling Point °C max	280

Packaging

200 litre drums
20 litre pails

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his own use. The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/12/2011	Supersedes: New	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by: