



Document Number:

TDS 088

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

VISCOL ROCKDRILL OIL 100, 150, 320

Description & Characteristics :

Viscol Rockdrill oils are high viscosity index oils blended with anti-wear and anti-corrosion additives. These oils are used extensively on wagon drills.

Performance Benefits :

Viscol Rockdrill Oils have good resistance to water-wash and maintain excellent lubrication. Ideal protection against rust and corrosion, have good extreme pressure and anti-wear properties.

Application :

Viscol Rockdrill Oils for percussion tools particularly on wagon drill units.

Physical Properties :

ISO GRADE	100	150	320
Viscosity cSt @ 40°C	90 - 110	150	315
Flash Point (COC)	230	240	255
Timken OK Load . . . kg	27	27	28

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

Page: 1/1	Date: 15/12/2014	Supercedes: New	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by: