



Document Number:

**TDS089**Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046P.O Box 71382, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
RooihuiskraalTel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)***VISCOL ROLLING N60**

Rolling N60 is a compounded roll oil ready for use as delivered to the customer. It is made with base oils low in sulphur and other impurities, which ensures excellent performance in both ferrous and non-ferrous mills, as well as freedom from metal staining. The additives used have been carefully selected to give maximum performance in the applications for which the oil is recommended. Rolling N60 has excellent filterability characteristics in circulating systems, even with the finest precoat filtration.

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES
Ash Content	% m/m	ASTM D 482	NIL
Copper Corrosion (3h @ 100°C	-	ASTM D 130	1B
Density @ 20°C	Kg/m <sup>3</sup>	ASTM D 4052	867.7
Neutralisation Number	Mg KOH/g	ASTM 974	0.1
Odour	-	Olfactory	Mild
Pour point	°C	ASTM D 97	-7
Viscosity @ 40°C	cSt	ASTM D 445	8.44

**APPLICATION**

N60 can be used:

- As a non-staining oil for cold-rolling copper alloys such as brass and German silver.
- For cold rolling carbon steel and stainless steel grips
- As a hydraulic oil in specially designed low viscosity, low pressure (below 100 atmospheres) hydraulic systems of rolling mills to avoid contamination of the roll oil fill by conventional hydraulic oils.
- In all types of mills including multi-roller mills such as the Sendzimir and Sundwig, where it can also be used to lubricate the mill bearings.

**PACKAGING**

N60 is a light yellow fluid available in bulk, 210 litre drums and 20 litre pails.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/12/2011	Supercedes: Rev 01	
SOP ref: Rev 01	Compiled by: Alex Hime	Checked by:	Authorised by: