



Document Number:

**TDS 114**

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za

**SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)*

## VISCOL WIRE ROPE SPRAY 30, 200, 200T, 60/40

### Description & Characteristics

Viscol Wire Rope Spray Oils are specially formulated adhesive lubricants for the maintenance of wire ropes. They contain anti-wear, anti-rust, mild extreme pressure additives and deep penetrating wet ability agents.

### Performance Benefits

The additive treatment in Viscol Wire Rope Spray oils protects the rope against water wash off and penetrates deep into the rope guarding against corrosion. The corrosion protection is excellent.

### Application

Viscol Wire Rope Spray oil contains a solvent and is applied by spray leaving behind a durable film of corrosion protection once most of the solvent has evaporated. It is applied at ambient temperature on clean rope surfaces such as hoist, guide, head and tail ropes and the like.

### Typical Physical Properties

VISCOL WIRE ROPE SPRAY	30	200	200T	60/40
Density @ 20 deg C.....kg/L	0,800	0,879	0,885	0.820
Applied Viscosity @ 40 deg C....mm2/sec	32	80	85	35
Service Viscosity @ 40 deg C...mm2/sec	120	185	200	195
Flash Point (COC) (deg C)	65	68	85	65
Pour Point (deg C)	-20	-16	-10	-18

Viscol Wire Rope Spray 200T has an added tackifier.

### Summary

- ❖ Applied – low viscous oil
- ❖ Spray - easy application
- ❖ Prevention - water wash off
- ❖ Good corrosion prevention

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his/her own use.

Page: 1/1	Date: 15/12/2011	Supercedes: New
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:
		Authorised by: