



Document Number:

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

TDS121

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

PRODUCT DATA SHEET

XD RUST PREVENTATIVE

Description : The product has been developed to meet the requirements for the protection of steel tubes and machined components whilst in storage against the effects of corrosion. It offers excellent corrosion protection and de-watering.

Method of use: Various methods of application are possible to achieve the necessary coating these include spray, dip, brush, drip feed and wiper.

Applications: For steel tubes and profiles, machined components, body panels etc. Where indoor or covered storage is required for a period of three to six months.

Qualifications: This product can be used to significantly increase a products resistance to atmospheric corrosion and rusting. The method of application and surface condition are important in order to obtain the desired storage or transit time.

Appearance: Amber brown slightly turbid fluid.

Typical density @ 20c: 0.800g/ml

SPECIFICATIONS	XD
ACTIVE INGREDIENT	+/- 30%
DE-WATERING	Yes
SALT SPRAY 5% (Astm B117)	168 hours
HUMIDITY CABINET	900 + hours
FLASH POINT	45 Deg C
RESIDUE TYPE	soft/waxy

Overview:

A solvent based temporary corrosion protective free from chlorinated hydrocarbons. XD gives a soft / waxy film upon evaporation of the solvent. It has proved successful when used on seam welded cold rolled steel tubes and profiles as a corrosion prevention aid in storage.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use. The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 10/10/2011	Supersedes: Rev 01
SOP ref:	Compiled by: Alex Hime	Checked by:
		Authorised by: