



Document Number:

TDS0122Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
(in accordance with ISO 9001 & 14001)

INFRASTRIP

Product Description:

A medium viscosity petroleum based mould and shutter releasing agent. Boosted additives ensure a good clean strip. Non evaporation agents prevent loss of product whilst moulds and shutters are in the sun. The resultant concrete finish is smooth with minimum blowholes. Infrastrip may be applied by spray, swab or brush.

Physical Properties:

Colour – Straw coloured
Viscosity – typ. 28 – 32 Centistokes @ 40 ° C
Flash point – typ. 200
Freezing Point – Typ. -36
Chlorine - none

Product Application:

1. Steel shutters.
2. Wood moulds.
3. Fibreglass shutters.
4. Plastic moulds.

Coverage:

The coverage when spraying Infrastrip is estimated to be around 40 to 80m² depending on the porosity of the surface.

Product Packaging:

20 litre and 210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects, especially in those difficult situations where a special formulation may be required. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 15/05/2014	Supersedes: Rev 0	
SOP ref: Rev 0	Compiled by: Alex Hime	Checked by:	Authorised by: