



Document
Number:

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

TDS127

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

SS Soluble

Description and Characteristics

SS Soluble is a soluble mould release oil for the production of railway sleepers, lintels, pre-cast fencing and similar intricate shaped moulds. Specifically formulated for timber, plywood and rubber/plastic moulds, but may also be used on metal ones. The additives used in SS Soluble allows for the mixing of water 4:1 and enhances the releasing properties, protects the mould from staining and provides an extremely clean release after curing. Add the water to the oil. Prepare the moulds a few hours before casting and use within a day.

Physical Characteristics

Viscosity at 40°C cST	28
Specific Gravity at 20°C kg/1	0.85
Open cup flash point ASTM D92°C	65 Neat

Benefits

Extremely good releasing properties.
Non- staining of pallets.
Good coverage.
Economical.

Application

Can be applied by swab, brush or spray.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own

Page: 1/1	Date: 15/12/2011	Supersedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: