



Document
Number:

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

TDS 140

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

VISCOL GL4 80W AUTOMOTIVE GEAR OIL

Description & Characteristics:

This is a quality gear lubricant specially recommended for gearboxes providing a stable lubricating film and minimizes wear. It contains sulphur-phosphorus EP levels at GL4 requirements and other additives exceeding the requirements of the U.S. Military Specifications MIL-L-2105.

VISCOL GL4 80W AUTOMOTIVE GEAR OIL	
Viscosity @ 40°C(cSt)	94,1
Viscosity @ 100°C(cSt)	11.3
Viscosity Index	110
Flash Point(°C)	212
Pour Point(°C)	-25

Performance Level:

API Service Classification GL-4
MIL-L-2105
Approved by Ford, Volkswagen and ZF TE-ML 17A
Daimler-Benz (SAE 80W) 235.1

Benefits:

1. Full protection to transmissions with bronze components.
2. Excellent low temperature fluidity.
3. Easy gear change.
4. Major equipment Builder acceptance.

Applications:

Suitable for transmissions, manual transmissions, and axle drives with normal to high loading for which GL4 is required.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his own use.

Page: 1/1	Date: 15/12/2011	Supersedes: New
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:
		Authorised by: