



Document
Number:

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 71382, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

TDS141

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

PRODUCT DATA SHEET

Eurosyn Q

Description

Eurosyn Q 10 is a semi-synthetic water extendible cutting fluid. It is manufactured with biocides, foam suppressants and extreme pressure additives, and it is free from sodium nitrite and phenols.

Directions for Use

Eurosyn Q 10 may be considered for use on steels, cast iron, yellow metals and aluminium and will provide protection for stored and semi-finished components against corrosion.

Add the concentrate to the water while stirring at the recommended dilution rates.

Recommended Treatment Rates:

Automatic machines	3.0%
Turning	3.0%
Sawing	5.0%
Milling	4.0%
Thread cutting	8.0%

Technical Data

Appearance	Blue fluid
Density @ 20°C g/ml	1.01
pH Value @ 5%	9.6

Overview

Eurosyn Q 10 is biostable, carefully selected components with a wide range of effectiveness, ensuring a long service life when compared to conventional products.

Biostable technology ensures a long problem-free service life. This results in lower disposal costs and reduced downtime.

As with all lubricants, good housekeeping and system maintenance are important to ensure the satisfactory working life of the product.

The product advantages may be summarized as follows: -

High levels of corrosion and microbial inhibition.

User friendly.

Stable clear solutions tolerant to hard waters.

Cost effective at working dilutions.

Page: 1/1	Date: 15/12/2011	Supercedes: Rev 01	
SOP ref: Rev 02	Compiled by: Alex Hime	Checked by:	Authorised by: