



Document Number:

**TDS 148**Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046P.O Box 7182, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
RooihuiskraalTel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)*

## Garage Gold Synthetic 5W30/5W40 API SN

### Description:

Garage Gold Synthetic Multigrade engine oil is recommended for all types of modern vehicles, including high-performance turbo-charged, supercharged petrol and diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks. Garage Gold is Viscol's popular synthetic brand specifically blended for private workshops and garage mechanics servicing vehicles which traditionally used to be maintained by OEM dealer principles. This high end oil is blended using fully synthetic base oils with a passenger car oil additive developed to formulate with detergent dispersant, antiwear, oxidation inhibitor and a viscosity index improver of high quality "Mid SAPS" with passenger car petrol and diesel performance.

### Performance benefits:

Viscol Multigrade Engine Oils keep operating costs low and ensure maximum engine life for the following reasons:

- They keep the engine clean internally and ensure full oil flow circulation to give maximum protection.
- They keep the piston rings and valves moving freely and so ensure maximum mechanical efficiency of the engine.
- They reduce engine wear to a minimum because they contain effective anti-rust, anti-corrosion and anti-wear additives.

### Performance Level:

<b>5w30</b>	<b>5w40</b>
API SN	API SN
ACEA C2/C3 -16	ACEA C3-16
MB 229.31/51/52	MB 229.31/229.51
BMW LL-04	dexos™2 gen 1
VW 505 01/505 00	
dexos™2	

Page: 1/2	Date: 15/12/2020	Supersedes: New	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by:



Document Number:

**TDS 148**Viscol cc  
Reg No: 1987/028096/23  
Vat Reg: 4380103046P.O Box 7182, Centurion, 0046  
130 Sarelbaard Crescent  
Gateway Industrial Park  
RooihuiskraalTel: (012) 661 9888  
Fax: (012) 661 9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with ISO 9001 & 14001)***Specifications:**

SAE GRADE	5W30	5W40		
Density @ 20°C	0.850	0.855		
Viscosity cSt @ 40°C	68.5	80		
Viscosity cSt @ 100°C	11.3	13.7		
Viscosity Index	164	176		
Flash Point (COC)°C	228	231		
Pour Point (°C)	-42	-51		
Total Base Number, mg KOH/g	10	11.8		

**Application:**

Synthetic Engine Oils are recommended for use in all petrol engines and in normally aspirated and supercharged light diesel engines.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 2/2	Date: 15/12/2020	Supercedes: New	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by: